

Making our mark on rural ustralia.



Webster Silos

Legendary Australian-made Webster Silos & Materials Handling Equipment for grain and fertiliser products.

Manufactured by Ahrens and erected on site, Webster Silos are designed and engineered for strength, durability and to meet Australian Standards in safety.

Providing grain and storage solutions throughout the Queensland and NSW grain belt for more than 35 years.



Ahrens

Elevated Webster silo range – specifications

Base Diameter (m)	Rows High	Approx Tonnes	Cubic Cap (m ³)	Approx Height (m)	Auger (m)	Price \$	
2.244 (7')	1	4.0	5.1	2.75	5.1 (17')		
	2	6.7	8.5	3.60	6.7 (22')		
	3	9.4	11.8	4.45	8.2 (27')		
	4	12.1	15.2	5.30	9.8 (32')		
2.992 (10')	1	8.0	10.1	3.18	5.9 (19')		
	2	12.8	16.0	4.03	7.5 (25')		
	3	17.6	21.0	4.88	9.0 (30')		
	4	22.0	27.0	5.73	10.6 (35')		
3.740 (12')	1	13.8	17.3	3.61	6.7 (22')		
	2	21.0	26.0	4.46	8.3 (27')		
	3	28.0	35.0	5.31	9.8 (32')		
	4	36.0	45.0	6.16	11.5 (38')		
	5	43.0	54.0	7.01	13.1 (43')		
	6	51.0	63.0	7.86	14.6 (48')		
4.488 (15')	1	21.0	27.0	4.05	7.5 (25')		
	2	32.0	40.0	4.90	9.1 (30')		
	3	43.0	53.0	5.75	10.7 (35')		
	4	54.0	67.0	6.60	12.3 (40')		
	5	64.0	80.0	7.45	13.8 (45')		
	6	75.0	94.0	8.30	15.4 (51')		
5.984 (20')	3	83.0	104.0	6.61	12.2 (40')		
	4	102.0	127.0	7.46	13.8 (46')		
	5	121.0	151.0	8.31	15.4 (51')		
	6	140.0	175.0	9.16	17.0 (56')		
	7	159.0	199.0	10.01	18.6 (61')		
	8	179.0	223.0	10.86	20.2 (66')		
	9	198.0	247.0	11.71	21.7 (71')		
	10	217.0	271.0	12.56	23.3 (77')		
	6.730 (22')	5	158.0	197.0	8.74	16.2 (53')	
		6	182.0	227.0	9.59	17.8 (59')	
7		206.0	257.0	10.44	19.4 (64')		
8		230.0	288.0	11.29	20.9 (69')		
9		254.0	318.0	12.14	22.5 (74')		
10		279.0	348.0	12.99	24.1 (79')		
7.480 (24')		5	200.0	249.0	9.17	17.0 (56')	
		6	230.0	287.0	10.02	18.6 (61')	
		7	259.0	324.0	10.87	20.2 (66')	
		8	289.0	362.0	11.72	21.8 (72')	
	9	319.0	399.0	12.57	23.4 (77')		
	10	349.0	436.0	13.42	24.9 (82')		
8.976 (30')	6	345.0	431.0	10.89	20.2 (66')		
	7	388.0	485.0	11.74	21.8 (72')		
	8	431.0	539.0	12.59	23.4 (77')		
	9	474.0	593.0	13.44	24.9 (82')		
	10	517.0	647.0	14.29	26.5 (87')		
	11*	570.0	712.0	15.69	29.2 (96')		
	12*	613.0	766.0	16.54	30.7 (101')		
13*	656.0	820.0	17.39	32.3 (106')			

Silo specifications subject to change without notice. Capacities nominal only and based on product 800kg/m³. Capacities and dimensions based on 30° conical base (* 35° conical base). Outlet diameter 300mm. Discharge height 600mm.

Standard Features

- Fully galvanised roof and wall structure
- Heavy duty conical base and support structure
- Fully bolted design ensuring long life
- Base manhole and inspection hatch at eave
- Outlet slide control lever
- Agricultural access ladder, including roof ladder
- Large auger hopper
- Easily transported to remote sites

Optional Features

- Aeration equipment
- Silo sealing
- Sight glasses
- Ground control lever for inlet lid operations
- Commercial access ladders and platforms
- Conical base angles available in 35°, 45° and 55°
- Fertiliser silos with epoxy treatment and SS bolts



1800 810 420
www.ahrens.com.au
 or contact your local dealer.



Ahrens